

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

Safety Data Sheet

1. Identification

Product name	Wheel Dust Blocker (Coating)
Product code	02076A
Manufacturer	Soft99 Corporation
Address	6-5, Tanimachi 2-Chome, Chuo-ku, Osaka, 540-0012, Japan
Department	Research & Development
Telephone	06-6942-6958
Product use	Antifouling coating for automobile aluminium wheels
Date of creation	2014/5/26
Date of revision	2021/3/16

2. Hazard identification

GHS classification	
Aerosol	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (Single exposure)	Category 2 (central nervous system, systemic toxicity)
Specific target organ toxicity (Single exposure)	Category 3 (drowsiness or dizziness)
Specific target organ toxicity (Repeated exposure)	Category 2 (blood)

Note: Classifications not shown here are either not applicable or cannot be classified due to lack of data.

GHS label symbols



Signal word **Danger**

Hazard statements

- H222 Extremely flammable aerosol
- H229 Pressurized container: may burst if heated
- H361 Suspected of damaging fertility or the unborn child
- H371 May cause damage to organs
- H336 May cause drowsiness or dizziness
- H373 May cause damage to organs through prolonged or repeated exposure

Precautions

- [Safety Measures]
- P201 Obtain special instructions before use.
 - P202 Do not handle until all the safety precautions have been read and understood.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
NO SMOKING!
 - P211 Do not spray on an open flame or other ignition source.
 - P240 Ground and bond container and receiving equipment.
 - P243 Take action to prevent static discharges.
 - P241 Use explosion-proof [electrical/ventilating/lighting/etc.] equipment.
 - P242 Use non-sparking tools.
 - P251 Do not pierce or burn, even after use.
 - P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 - P271 Use only outdoors or in a well-ventilated area.
 - P270 Do not eat, drink or smoke when using this product.
 - P264 Wash hands thoroughly after handling.
 - P280 Wear protective gloves/protective clothing/eye protection/face shield.
- [First aid measures]
- IF INHALED:
- P340 Remove victim to fresh air and keep comfortable for breathing.
 - P312 Call a POISON CENTER/doctor/physician, if you feel unwell.
- IF SWALLOWED:
- P330,331 Do NOT induce vomiting. Rinse mouth.
 - P310 Immediately call a POISON CENTER/doctor/physician.
- IF IN EYES:
- P351 Rinse cautiously with water for at least 15 minutes.
 - P338 Remove contact lenses, if present and easy to do. Continue rinsing.
 - P313,337 If eye irritation persists, get medical advice/attention.
- IF ON SKIN (or hair):
- P361,353 Remove immediately all contaminated clothing. Rinse skin with water [or shower].

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

P308,311 If exposed or if you feel unwell: Call a POISON CENTER/doctor/physician.
P314 Get medical advice/attention if you feel unwell.
P378 Use suitable extinguishing methods.
[Storage]
P102,405 Keep out of reach of children. Store locked up.
P410,412 Protect from sunlight. Do not expose to temperatures exceeding 40°C.
P403,235 Store in a well-ventilated place. Keep cool.
[Disposal]
P501 Dispose of product and containers in accordance with all applicable local, state, federal, and international regulations.

3. Composition/information on ingredients

Classification of the substance or mixture

- Mixture

Ingredient	(wt%)	CAS No.
(Main ingredients)		
Siloxane	50-60	Non-disclosed
Isopropanol	< 5	67-63-0
Octamethylcyclotetrasiloxane (Aerosol propellant)	10-20	556-67-2
Propane	25-35	74-98-6
Butane		106-97-8
Isobutane		75-28-5

4. First-aid measures

INHALATION:

- Remove victim to fresh air and keep comfortable for breathing.
- Get medical advice/attention if symptoms persist.
- If experiencing symptoms of drowsiness or dizziness, remove victim to fresh air and keep comfortable for breathing.
- If vomiting occurs, keep head low so that stomach content does not enter the lungs.
- If breathing difficulties develop, oxygen should be administered by qualified personnel.
- Symptoms may arise some time after inhalation.
- If any of the above symptoms occur, get immediate medical advice/attention.

SKIN CONTACT

Although not a poison or serious irritant, if liquid contacts the skin, do the following.

- Wash affected area with large amounts of water and soap.
- Take off contaminated clothing.
- Keep away from open fire, sparks and other ignition sources.

EYE CONTACT

- Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes.
- Ensure thorough flushing behind the eyelids, and all around the eye.
- Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists, get medical advice/attention.
- If intense pain persists, get medical advice/attention immediately.

INGESTION

- Immediately rinse mouth thoroughly.
- Get medical advice/attention immediately
- Do NOT induce vomiting.
- If a child is suspected of swallowing this product, seek medical treatment immediately.
- If necessary, use artificial ventilation or oxygen.

Most serious sign(s) and/or symptom(s)

- None known.

Notes to doctor

- Not specified.

5. Fire-fighting measures

Suitable extinguishing media

- Powder, foam, carbon dioxide

Unsuitable extinguishing media

- DO NOT use water.
- Using mist for cooling is acceptable, but do not aim a stream of water at the fire.

Specific hazards with regard to fire-fighting

- Fumes emitted from the burning product contain poisonous gases such as carbon monoxide, nitrogen oxides, etc. When extinguishing, take care not to inhale the smoke.
- This product has a risk of explosion when on fire. Escape immediately.

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

Particular fire fighting measures

- If possible, perform extinguishing procedures upwind from the fire.
- Evacuate all non-essential personnel from immediate area.
- In case of fire nearby, move product to a safe place.
- Do not admit non-essential people to the area of the fire.
- Apply water from a safe distance to cool and protect surrounding area.
- Avoid discharges of environmentally harmful substances.
- Container may rupture at high temperatures. Extinguish from an appropriate distance.

Protection for firefighters

- Wear proper protective gloves, goggles and mask.
- Perform extinguishing procedures upwind from the fire. Avoid breathing fumes. Use breathing equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- If indoors, ensure sufficient ventilation until the clean-up has been completed.
- Wear suitable protective equipment such as protective mask, gloves, goggles and apron during cleanup operation.
- Prevent others from entering the area with a rope, etc.
- Take suitable measures to avoid contact with skin, inhalation of fumes and dust, etc.
- Work from upwind, evacuate people from downwind of the release.
- As a precaution against fire, prepare a fire extinguisher.
- The area of the spillage may be slippery. Take care.

Environmental precautions

- Do not release into rivers, sewers, or other routes that may damage the environment.

Methods and materials for containment and cleaning up

- If in small quantities, absorb the spill (using sand, sawdust, rags, etc.) and thoroughly wipe up the remnants using cloth or rags. Move contaminated material to a sealed container.
- If in large quantities, contain the spill with dykes (sandbags, etc.) before cleaning up.
- Deal with contaminated material and waste according to the appropriate regulations.

Prevention of secondary disasters

- To prevent spreading or accidents, inform the relevant person(s) immediately.
- Immediately eliminate all ignition sources, and prepare extinguishing media.
- Use non-sparking tools.

7. Handling and storage

Handling

- Read the instructions and take all precautions before use.
- Do not use except for intended purpose.
- Obtain special instructions before use.
- Do not handle this product until all safety precautions have been read and understood.
- Do not pierce or burn, even after use.
- Do not spray onto flames or very hot surfaces.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
- Ground and bond container and receiving equipment.
- Take action to prevent static discharges.
- Use non-sparking tools.
- Use explosion-proof [electrical/ventilating/lighting/etc.] equipment.
- Do not discharge for longer than the prescribed time.
- Do not use in a room with open flames.
- Prevent spilling and splashing. Do not allow unnecessary evaporation.
- Avoid breathing dust/fumes/gas/mist/vapors/spray.
- Do not discharge towards people. Do not inhale discharged material.
- Use only outdoors or in a well-ventilated area.
- Do not eat, drink or smoke when using this product.
- Wash hands thoroughly after handling.

Storage

- Store according to instructions on the product.
- Protect from sunlight. Do not expose to temperatures exceeding 40°C.
- Store in a cool, well ventilated area.
- Store in a locked area.

Packaging

- Not specified.

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

8. Exposure controls/personal protection

Occupational exposure guidelines

	ACGIH (TLV-TWA)	(TLV-STEL)
Isopropanol	200 ppm	400 ppm
Propane	1000 ppm	
Butane	800 ppm (2005)	
Isobutane	250 ppm (2009)	

Protective equipment

- If vapors, mist, or smoke is produced, provide ventilation.
- Provide local exhaust ventilation when using indoors.
- Fully ventilate indoor environments. If poorly ventilated, use local exhaust ventilation.

Personal protective equipment

Respiratory

- Wear dust respirator, gas mask or organic solvent gas mask as needed.

Hand

- Wear protective gloves, solvent resistant gloves or vinyl gloves as needed.

Eye, face

- Wear protective glasses, goggles or mask as needed.

Body, skin

- Wear protective equipment as clothing or boots or apron as needed.

9. Physical and chemical properties

(for base liquid excluding propellant, unless specified)

Physical state	: Liquid
Color	: Transparent, pale white
Odor	: Characteristic odor
Melting point	: No data
Boiling point and range	: 150–180 °C (by analogy)
Flammability	: Flammable
Combustion/explosion limits	: No data
Flash point	: 35 °C
Auto-ignition temperature	: No data
Decomposition temperature	: No data
pH (25°C)	: No data
Solubility in water	: Insoluble
Vapor pressure (25°C Product internal pressure)	: 0.23±0.05 MPa (including propellant)
Relative density (25 °C)	: 0.844±0.02
Relative vapor density	: No data
(Propellant)	
Physical state	: Liquefied gas
Color	: Colorless
Odor	: Characteristic odor
Melting point	: -188 °C (propane), -138 °C (butane), -160 °C (isobutane)
Boiling point and range	: -42 °C (propane), -0.5 °C (butane), -12 °C (isobutane)
Flammability	: Flammable
Combustion/explosion limits	: 1.8–9.5 vol% (propane, butane, isobutane)
Flash point	: -104 °C (propane), -72 °C (butane), -81 °C (isobutane)
Auto-ignition temperature	: 450 °C (propane), 365 °C (butane), 460 °C (isobutane)
Relative vapor density (Air=1)	: 1.6 (propane), 2.1 (butane), 2.0 (isobutane)

10. Stability and reactivity

Chemical stability	• Stable under normal conditions.
Possibility of hazardous reactions	• Reacts vigorously with strong oxidants. May cause fire or explosion.
Conditions to avoid	• Heating and heat sources, open flames • Avoid contact with strong oxidizing agents.
Incompatible materials	• Strong oxidants
Hazardous decomposition products	• None known.
Other	• None known.

11. Toxicological information

There is no product test data.

Siloxane	(Oral)	LC50 > 5000 mg/kg (Rat)
Isopropanol	(Oral)	LD50 3437 mg/kg (Rat)
Octamethylcyclotetrasiloxane	(Oral)	LD50 > 4800 mg/kg (Rat)

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

Isopropanol	(Dermal)	LD50 4059 mg/kg (Rabbit, CERI(1999))
Octamethylcyclotetrasiloxane	(Dermal)	LD50 > 2375 mg/kg (Rat)
Isopropanol	(Inhalation)	LD50 72600 mg/m ³ /4h (Rat)
Octamethylcyclotetrasiloxane	(Inhalation)	LD50 36000 mg/m ³ (Rat)
Isobutane	(Inhalation)	LC50 52 mg/L/48h (Mouse)
Acute toxicity (Oral)	Classification not possible 30–40 percent of the mixture consists of ingredient(s) of unknown acute oral toxicity.	
Acute toxicity (Dermal)	Classification not possible 80–90 percent of the mixture consists of ingredient(s) of unknown acute dermal toxicity.	
Acute toxicity (Inhalation)	Classification not possible 90–100 percent of the mixture consists of ingredient(s) of unknown acute inhalation toxicity.	
Skin corrosion/irritation	Classification not possible	
Serious eye damage/irritation	Classification not possible	
Respiratory sensitization	Classification not possible	
Skin sensitization	Classification not possible	
Germ cell mutagenicity	Classification not possible	
Carcinogenicity	Classification not possible	
Reproductive toxicity	Suspected of damaging fertility or the unborn child (Category 2)	
Specific target organ toxicity (Single exposure)	May cause damage to organs (Category 2)	
Specific target organ toxicity (Single exposure)	May cause drowsiness or dizziness (Category 3)	
Specific target organ toxicity (Repeated exposure)	May cause damage to organs through prolonged or repeated exposure (Category 2)	
Aspiration hazard	Classification not possible	

Hazard category information

Ingredient	Acute toxicity Oral	Acute toxicity Dermal	Acute toxicity Inhalation	Skin corrosion /irritation	Serious eye damage /eye irritation
Siloxane	-				
Isopropanol	-	-	-(vapor)	-	2
Octamethylcyclotetrasiloxane	-	-		-	-
Propane	-	-	-(gas)	-	
Butane	-	-	-(gas)	-	
Isobutane			4(gas)	-	-

Ingredient	Respiratory sensitization	Skin sensitization	Germ cell mutagenicity	Carcinogenicity	Reproductive toxicity
Siloxane					
Isopropanol			-	-	
Octamethylcyclotetrasiloxane		-	-		
Propane					
Butane					
Isobutane					

Ingredient	Specific target organ toxicity		Aspiration hazard
	Single exposure	Repeated exposure	
Siloxane			
Isopropanol	1,3(R)	1,2	
Octamethylcyclotetrasiloxane			
Propane	3(D)		-
Butane	3(D)		-
Isobutane	2,3(D)		-

Blank: Not classified/
Classification not possible
- : Not classified
R: Respiratory irritation
D: Drowsiness or dizziness

For the purpose of GHS classification of the product, in some cases the classification of the raw materials is used. Toxicological data for each component are reference values.

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

12. Ecological information

There is no product test data.

Hazardous to the aquatic environment, acute hazard

Isopropanol

LC50 > 100 mg/L/96h (Oryzias latipes var.)

Classification not possible

90–100 percent of the mixture consists of ingredient(s) of unknown acute hazards to the aquatic environment.

Hazardous to the aquatic environment, chronic hazard

Classification not possible

80–90 percent of the mixture consists of ingredient(s) of unknown chronic hazards to the aquatic environment.

Hazard category information

Ingredient	Hazardous to the aquatic environment	
	Acute hazard	Chronic hazard
Siloxane		
Isopropanol	–	–
Octamethylcyclotetrasiloxane		4
Propane		
Butane		
Isobutane		

Blank: Not classified/Classification not possible
– : Not classified

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Harmful to the ozone layer

No information available.

13. Disposal considerations

- Use all contents before disposal.
- Read instructions for and use the gas release cap to discharge excess gas in an outside area, away from flames.
- Dispose of contents/container in accordance with applicable regional, national, and local laws and regulations.

14. Transport information

UN class 2.1 Flammable gases

UN number UN1950 AEROSOLS

Specific safety measures and condition for transportation

- Strictly no sources of ignition
- Check for breakages and leaks
- Prevent luggage from collapsing
- Wrap, display and transport according to the law.
- Avoid direct sunlight
- Do not wet
- Pack upright
- Do not place on hot surfaces (outside during summer, etc.)
- Handle carefully to avoid shocks and violent movements

15. Regulatory information

Follow the applicable regional, national, and local laws and regulations.

16. Other information

References

Hazard communication of chemicals based on GHS–Labelling and Safety Data Sheet (SDS) JIS Z7253(2019)

GHS Classification Results (NITE website, Japan)

Supplier's SDS

Guide to SDS Composition for Auto Chemicals (JACA)

REF. No. 02076A	Wheel Dust Blocker (Coating)	Created date	2014/5/26
Ver. 5	SOFT99 corporation	Rev. date	2021/3/16

The information contained herein is based on current knowledge and experience; no responsibility is accepted for the information being sufficient or correct in all cases. Users should consider these data only as a supplement, and must make independent determinations of suitability and completeness of information from all sources to ensure proper use and disposal of these materials, the health and safety of employees/customers, and protection of the environment.